72220 D.S. PTO 08777557


9 truncated truncated X 2 5-6-55ypen 5-6-5 system 65 8-83

Bo truncated 20 02 3 5-6-5 sysku 92 8-8-8

F/6/

			4-						_		•	08777	557
	<u>8 BIT</u>												
												2/30/ 1	96 -
	7	6	5	4	3	2	1	0	4	3			
	0	0	0	0	0	0	0	0	0	0	0	0	0
1/8	0	0	0	0	0	0	0	1	0	0	0	0	0
(2/8	0	0	0	0	0	0	1	0	0	0	0	0	0
3/8	0	0	0	0	0	0	1	1	0	0	0	0	0
A 2 4/8	0	0	0	0	0	1	0	0	0	0	0	0	0
) 5/8	0	0	0	0	0	1	0	1	0	0	0	0	0
/ 6/8	0	0	0	0	0	1	1	0	0	0	0	0	0
(7/8	0	0	0	0	0	1	1	1	0	0	0	0	0
>	0	0	0	0	1	0	0	0	0	0	Ô	0	1
(1/8	0	0	0	0	1	0	0	1	0	0	0	0	1
\ 2/8	0	0	0	0	1	0	1	0	0	0	0	0	1
3/8	0	0	0	0	1	0	1	1	0	0	0	0	1
A < 4/8	0	0	0	0	1	1	0	0	0	0	0	0	1
) 5/8	0	0	0	0	1	1	0	1	0	0	0	0	1
(6/8	0	0	0	0	1	1	1	0	0	0	0	0	1
7/8	0	0	0	0	1	1	1	1	0	0	0	0	1
	0	0	0	1	0	0	0	0	0	0	0	1	0
1/8	0	0	0	1	0	0	0	1	0	0	0	1	0
					•						•		
									The state of the s				
					•						•		
					•				l)		•		

FIG. 2



Secription .

		X A d d r										
		0	1	2	3	4	5	6	7			
	0	0	4	1	5	0	4	1	5			
Y	1	6	2	7	3	6	2	7	3			
Α	2	1	5	0	4	1	5	0	4			
d	3	7	3	6	2	7	3	6	2			
d	4	0	4	1	5	0	4	1	5			
r	5	6	2	7	3	6	2	7	3			
	6	1	5	0	4	1	5	0	4			
	7	7	3	6	2	7	3	6	2			







F16.5

•	tsystem)	[0]	0	0	0	\mathcal{C}		
	(6 b)	$\langle - $	ସ	0	0	~		٩
:	RAMP ((4)	0	0	~	~		Ġ
:	à	, w	۵	1)	\		1
64		FRAC	0	_	7	M		

_	[,	4
den.)	6	0	0	0	0	0	0	0	2	و ر
1545	\	อ	Ø	Ð	9	0	0	/_	_	
RAMP (5 bitsystem)	2	อ	0	Ð	0	0	2	_	~	
) d	T T	٥	0	0	5			_	_	
Ž	4 81	၁	0	Ð	9	/ <u> </u>	_		_	
UΣ	1"	9	0		/_			_		
	e	0	0	/-	_		_		_	
-	- IN	0,	/		. –		_	,	_	
-	J									_
×	1 RF	0	_	- 2	(%	4	- v	0	2	
		. [

72220 U.S.	PTØ
ן פַּכּון ווטש	

8 bit shade 0 →	0	0	0	0	0	0	0	o ^M	12/ 5 05 Out Shade 0
	0	0	0	0	0	0	0	1	1
	0	0	0	0	0	0	1	0	
	0	0	0	0	0	0	1	1	
64 →	0	0	0	0	0	1	0	0	← 63
·	0	0	0	0	0	1	0	1	
	0	0	0	0	0	1	1	0	
	0	0	0	0	0	1	1	1	
8 bit shade 8 →	0	0	0	0	1	0	0	0	←5 bit shade 1

FIG. 7